



MIAMI-DADE COUNTY, FLORIDA
METRO-DADE FLAGLER BUILDING

BUILDING CODE COMPLIANCE OFFICE
METRO-DADE FLAGLER BUILDING
140 WEST FLAGLER STREET, SUITE 1603
MIAMI, FLORIDA 33130-1563
(305) 375-2901
FAX (305) 375-2908

PRODUCT CONTROL DIVISION
(305) 375-2902
FAX (305) 372-6339

Paul Lautrup
Convalence Specialty Coatings LLC
25 Forge Parkway
franklin, MA - Massachusetts 02038

NOTICE OF PROPOSED ACTION

To: **Members of the Board of Rules and Appeals and
Convalence Specialty Coatings LLC, Applicant**

In accordance with Dade County Administrative Order 10-3, which governs the product review process, the Product Control Division of the Office of Code Compliance, intends to issue a Product Control Notice of Acceptance to Convalence Specialty Coatings LLC for Barricade Dry Step, No. 08-1103.07, to allow its use in Dade County and its municipalities.

To: **Members of the Board of Rules and Appeals:**

The documentation being provided to you represents the recommendation of the Product Control Division of the Office of Code Compliance in regards to the submittal of Convalence Specialty Coatings LLC for Barricade Dry Step, No. 08-1103.07. Under the provisions of Dade County Administrative Order 10-3, which governs the product review process. You must review this documentation. If within 20 days from the date of mailing, we do not receive any written objection stating the reason(s) for your disapproval, this product will be automatically approved.

To: **Convalence Specialty Coatings LLC, Applicant**

The Product Control Division of the Office of Code Compliance, in accordance with Dade County Administrative Order 10-3, which governs the product review process, has issued this notice of proposed action and intends to issue a Product Control Notice of Acceptance for your Barricade Dry Step, No. 08-1103.07, to be used in Dade County and its municipalities, unless a member of the Board of Rules and Appeals or yourself has any objections. Should you not be in accord with this notice of proposed action and wish to appeal our recommendation, you must make a written request, stating the reasons for your objection(s), to our office within 20 days of the date of mailing. Upon receipt of your written request a hearing date will be set so that you can present your objection(s) to the Board of Rules and Appeals.

Sincerely,

Jaime D. Gascon, PE
Chief, Product Control Division

DATE OF MAILING: 12/12/2008

MAILED BY:



**BUILDING CODE COMPLIANCE OFFICE (BCCO)
PRODUCT CONTROL DIVISION**

**MIAMI-DADE COUNTY, FLORIDA
METRO-DADE FLAGLER BUILDING
140 WEST FLAGLER STREET, SUITE 1603
MIAMI, FLORIDA 33130-1563
(305) 375-2901 FAX (305) 375-2908**

NOTICE OF ACCEPTANCE (NOA)

**Covalence Specialty Coatings, LLC.
d/b/a Berry Plastics Tapes and Coatings Division
25 Forge Parkway
Franklin, MA 02038**

SCOPE:

This NOA is being issued under the applicable rules and regulations governing the use of construction materials. The documentation submitted has been reviewed by the BCCO and accepted by the Building Code and Product Review Committee to be used in Miami Dade County and other areas where allowed by the Authority Having Jurisdiction (AHJ).

This NOA shall not be valid after the expiration date stated below. The Miami-Dade County Product Control Division (In Miami Dade County) and/or the AHJ (in areas other than Miami Dade County) reserve the right to have this product or material tested for quality assurance purposes. If this product or material fails to perform in the accepted manner, the manufacturer will incur the expense of such testing and the AHJ may immediately revoke, modify, or suspend the use of such product or material within their jurisdiction. BORA reserves the right to revoke this acceptance, if it is determined by Miami-Dade County Product Control Division that this product or material fails to meet the requirements of the applicable building code.

This product is approved as described herein, and has been designed to comply with the Florida Building Code and the High Velocity Hurricane Zone of the Florida Building Code.

DESCRIPTION: Barricade Dry Step

LABELING: Each unit shall bear a permanent label with the manufacturer's name or logo, city, state and following statement: "Miami-Dade County Product Control Approved", unless otherwise noted herein.

RENEWAL of this NOA shall be considered after a renewal application has been filed and there has been no change in the applicable building code negatively affecting the performance of this product.

TERMINATION of this NOA will occur after the expiration date or if there has been a revision or change in the materials, use, and/or manufacture of the product or process. Misuse of this NOA as an endorsement of any product, for sales, advertising or any other purposes shall automatically terminate this NOA. Failure to comply with any section of this NOA shall be cause for termination and removal of NOA.

ADVERTISEMENT: The NOA number preceded by the words Miami-Dade County, Florida, and followed by the expiration date may be displayed in advertising literature. If any portion of the NOA is displayed, then it shall be done in its entirety.

INSPECTION: A copy of this entire NOA shall be provided to the user by the manufacturer or its distributors and shall be available for inspection at the job site at the request of the Building Official.

This NOA consists of pages 1 through 4.

The submitted documentation was reviewed by Alex Tigera.

AT

**NOA No.: 08-1103.07
Expiration Date: 08/08/13
Approval Date:
Page 1 of 4**

ROOFING COMPONENT APPROVAL

Category: Roofing
Sub-Category: Underlayment
Material: Polypropylene

SCOPE:

This acceptance is for **Barricade Dry Step** as manufactured by Interwrap, Inc., as described in this Notice of Acceptance, for use with approved prepared roof assemblies.

PRODUCT DESCRIPTION:

<u>Product</u>	<u>Dimensions</u>	<u>Test Specification</u>	<u>Product Description</u>
Barricade Dry Step	48" x 250' rolls	ASTM D226 Type I	Woven synthetic polymer underlayment with one side coated with UV protected and slip resistant polymer stabilized polypropylene on both sides.

EVIDENCE SUBMITTED:

<u>Test Agency</u>	<u>Test Identifier</u>	<u>Test Name/Report</u>	<u>Date</u>
Intertek Testing Services	#3031783	TAS 104	02/19/03
	3119607COQ-003B	ICC-ES AC48	02/20/08
	3124826-01	ASTM E108	02/19/08
	3124826MID-007	ASTM E108	02/25/08
	3118010COQ-003	ASTM D226	02/20/08
	3130639COQ-002A	ASTM D226	02/20/08
	3146738COQ-003A	ASTM D226	04/22/08
	3146738COQ-003B	ASTM D 1876/ TAS 117	03/28/08

NOA No.: 08-1103.07
Expiration Date: 08/08/13
Approval Date:
Page 2 of 4

INSTALLATION SPECIFICATIONS: (Double Layer)**Barricade Dry Step**

1. Barricade Dry Step shall be installed in strict compliance with applicable Building Code.
2. Barricade Dry Step shall be installed with a minimum 24-inch head lap in a shingle layer fashion.
3. Barricade Dry Step shall be fastened with approved corrosion resistant tin-caps and 12 gauge 1 ¼" annular ring-shank nails, spaced 6" o.c. at all laps and one staggered row fastened 12" o.c. in the field of the roll.
4. Barricade Dry Step may be used with Asphaltic shingles, Wood shakes and shingles, Non-structural metal roofing, and quarry slate. , Barricade Dry Step shall not be used as roof tile underlayments.
5. For fire classification of specific roof assemblies using , Barricade Dry Step refer to a current Approved Roofing Materials Directory for fire ratings of this product.

BUILDING PERMIT REQUIREMENTS:

Application for building permit shall be accompanied by copies of the following:

1. This Notice of Acceptance.
2. Any other documents required by the Building Official or applicable building code in order to properly evaluate the installation of this material.

LIMITATIONS:

1. Fire classification is not part of this acceptance; refer to a current Approved Roofing Materials Directory for fire ratings of this product.
2. This acceptance is for prepared roofing applications. Minimum deck requirements shall be in compliance with applicable building code.
3. Barricade Dry Step shall be applied to a smooth, clean and dry surface with deck free of irregularities. All nails in the deck shall be carefully checked for protruding heads. Re-fasten any loose decking panels. Sweep the deck thoroughly to remove any dust and debris prior to application.
4. Barricade Dry Step shall not be hot mopped, refer to manufacturer's published literature for product compatibility.
5. Barricade Dry Step shall not be applied over an existing roof membrane as a recover system.
6. Barricade Dry Step shall not be left exposed as a temporary roof for longer than 30 days of application.
7. Barricade Dry Step are components used in roof system assemblies. Roof system assemblies are approved under a specific Notice of Acceptance. Refer to Prepared Roofing system Product Control Notice of Acceptance for listed approval of this product with specific prepared roofing products.
8. Barricade Dry Step may be used with any approved roof covering Notice of Acceptance listing Barricade Dry Step as a component part of an assembly in the Notice of Acceptance. If Barricade Dry Step is not listed, a request may be made to the Authority Having Jurisdiction (AHJ) or the Miami-Dade County Product Control Department for approval provided that appropriate documentation is provided to detail compatibility of the products, wind uplift resistance, and fire testing results.
9. All membranes or packaging shall bear the imprint or identifiable marking of the manufacturer's name or logo and the following statement: "Miami-Dade County Product Control Approved" or the Miami-Dade County Product Control Seal as shown below.

A black oval seal with the text "MIAMI-DADE COUNTY" in white on the top line and "APPROVED" in white on the bottom line.

MIAMI-DADE COUNTY
APPROVED

END OF THIS ACCEPTANCE

NOA No.: 08-1103.07
Expiration Date: 08/08/13
Approval Date:
Page 4 of 4