



POLYKEN® 243
Multi-Purpose Duct Tape


APPLICATIONS

- Superior performance on flex duct.
- Sealing standard duct work.
- General purpose packaging.
- Holding down fiberglass insulation materials.
- Condensation barrier in refrigeration assemblies.

FEATURES & BENEFITS

- Soft and conformable backing.
- Provides high tack and quick grab.
- Excellent tear characteristics.
- High performance in cold temperatures.
- Tested in accordance with UL 723.
- **Contributes toward satisfying EA (Energy & Atmosphere) and IEQ (Indoor Environmental Quality) credits under LEED®.****

CONSTRUCTION



PRODUCT DESCRIPTION

Single-Coated Construction

Backing:

- Polyethylene Coated Cloth

Adhesive:

- Rubber

Colors:

- Black, Silver

TEST DATA

Test	Typical Value	Typical Value (Metric)	Test Method
Total Thickness	10 mils	254.00 μ	ASTM D 1000
Adhesion to Steel	46 oz./in.	5.03 N/cm	PSTC-1
Adhesion to Backing	43 oz./in.	4.71 N/cm	PSTC-1
Tensile Strength	23 lb./in.	40.28 N/cm	ASTM D 1000
Maximum Performance Temperature	200 D F		
Flame Spread	10		
Smoke Developed	5		
VOC Content	<1 g/L		

Recommended storage conditions: 40-60% Humidity, 60°F-80°F

**Products are not reviewed or certified under the LEED® Rating System. LEED® credit requirements cover the performance of materials in aggregate, not the performance of individual products or brands. For more information on LEED®, visit www.usgbc.org/leed.

The information presented herein was prepared at BERRY PLASTICS CORPORATION (25 Forge Parkway Franklin, MA 02038) by qualified technical person. To Berry's knowledge it is true and accurate. However, the information and recommendations are furnished for these products with the understanding that the purchaser or user, as the case may be, will independently determine that the product is suitable for the intended use, and that such use complies with all applicable federal, state and local laws and regulations. The data are submitted only for the user's information and consideration, and do not constitute a warranty of any kind (including but not limited to a warranty of merchantability or of fitness for a particular purpose), or a representation for which BERRY PLASTICS assumes any responsibility.