



NASHUA® 327
Heavy Duty Foil Tape


APPLICATIONS

- Duct joint sealing for low, medium, and high pressure HVAC systems.
- Sheet metal repairs.
- A general purpose repair tape for aluminum siding, storage buildings, flashing, gutters, awnings, and other applications.

FEATURES & BENEFITS

- Very aggressive adhesive stays pliable and resists releasing.
- Instant air and water-tight bond to sheet metal, duct wrap barriers, duct board, and flexduct.
- High tensile strength.
- Paintable backing.
- Complies with VOC requirements of SCAQMD Rule 1168
- **Contributes toward satisfying EA (Energy & Atmosphere) and IEQ (Indoor Environmental Quality) credits under LEED®.****

CONSTRUCTION



PRODUCT DESCRIPTION

Single-Coated w/Liner Construction

Backing:

- 2 mil Aluminum Foil - Printed

Adhesive:

- Butyl Rubber

Liner:

- White LDPE

Colors:

- Aluminum

TEST DATA

Test	Typical Value	Typical Value (Metric)	Test Method
Total Thickness	17 mils	431.80 μ	ASTM D 1000
Adhesion to Steel	200 oz./in.	21.89 N/cm	PSTC-1
Mastic Thickness	15 mils	1.64 N/cm	PSTC-1
Tensile Strength	16 lb./in.	28.02 N/cm	ASTM D 1000
Maximum Performance Temperature	200 F		

Recommended storage conditions: 40-60% Humidity, 60°F-80°F

**Products are not reviewed or certified under the LEED® Rating System. LEED® credit requirements cover the performance of materials in aggregate, the performance of individual products or brands. For more information on LEED®, visit www.usgbc.org/leed.

The information presented herein was prepared at BERRY PLASTICS CORPORATION (25 Forge Parkway Franklin, MA 02038) by qualified technical personnel. To the best of Berry's knowledge it is true and accurate. However, the information and recommendations are furnished for these products with the understanding that the purchaser, as the case may be, will independently determine that the product is suitable for the intended use, and that such use complies with all applicable federal, state and local laws and regulations. The data are submitted only for the user's information and consideration, and do not constitute a warranty of any kind (including but not limited to a warranty of merchantability or of fitness for a particular purpose), or a representation for which BERRY PLASTICS assumes any legal responsibility.